WESTLAKE

Dealer contact:

WESTLAKE

Commercial Stainless Steel Refrigerator and Freezer
Commercial Glass door Refrigerated Showcase
Commercial Ice Machine

Intertek Intertek DOE ENERGY STAR 2 year WARRANTY Parts & Labor 6 year WARRANTY Compressor

WESTLAKE

Professional Kitchen Equipment Supplier

Fresh Your Life

Warehouse Address:
CA warehouse:
9180 Center Ave dock 14, Rancho Cucamonga, CA 91730
GA warehouse:
2760 Faith Industrial Dr BUFORD, GA 30518
NJ warehouse:
2301 cottontail lane dock 8-11 somerset NJ,08873
TX warehouse:
8630 Fallbrook Drive STE200 ,Houston,TX,77064

Reach in Top Mounted Refrigerator and Freezer Solid Door Series

WK-48R and WK-48F

WK-48RF(Combo)

WK-72R and WK-72F

WK-72RF(Combo)

Features

- Precise fan cooling system keeps food at safe temperature.
- Stainless steel interior and exterior,and with anti fringeprint function.
- Preinstalled heavy duty castors with brakes.
- Self-closing doors with 90 degrees-tay-open feature.Locks and keys included.

Certifications

Intertek Intertek

Technical Data

Model	Gross Capacity	Tempertaure	Dimension WxDxH inch	Voltage	Shelves	Certications
WK-48R	36 Cu.ft	33~41°F	48.4*31.5*77.9	115V/60Hz	6	ETL
WK-48F	36 Cu.ft	-8~0°F	48.4*31.5*77.9	115V/60Hz	6	ETL
WK-48RF	36 Cu.ft	33~41°F and -8~0°F	48.4*31.5*77.9	115V/60Hz	6	ETL
WK-72R	54 Cu.ft	33~41°F	72.8*31.5*77.9	115V/60Hz	9	ETL
WK-72F	54 Cu.ft	-8~0°F	72.8*31.5*77.9	115V/60Hz	9	ETL
WK-72RF	54 Cu.ft	33~41°F and -8~0°F	72.8*31.5*77.9	115V/60Hz	9	ETL

Commercial Grade Bottom Mounted Reach in Refrigerator and Freezer

Features

- Precise fan cooling system keeps food at safe temperature.
- Stainless steel interior and exterior,and with anti fringeprint function.
- Preinstalled heavy duty castors with brakes.
- Self-closing doors with 90 degree stay-open feature.Locks and keys included.

Certifications

Intertek Intertek ENERGY STAR

WKR-23B
WKF-23B

WKR-49B
WKF-49B

WKR-82B
WKF-82B

WKR-23BG

WKR-49BG

WKR-82BG

Technical Data

Model	Gross Capacity	Tempertaure	Dimension WxDxH inch	Voltage	Shelves	Certications
WKR-23B	23 Cu.ft	33~41°F	26.9*30.7*81.9	115V/60Hz	3	ETL,Energy Star
WKF-23B	23 Cu.ft	-8 ~0°F	26.9*30.7*81.9	115V/60Hz	3	ETL,Energy Star
WKR-23BG	23 Cu.ft	33~41°F	26.9*30.7*81.9	115V/60Hz	4	ETL,Energy Star
WKR-49B	49 Cu.ft	33~41°F	54.1*30.7*81.9	115V/60Hz	6	ETL,Energy Star
WKF-49B	49 Cu.ft	-8 ~0°F	54.1*30.7*81.9	115V/60Hz	6	ETL,Energy Star
WKR-49BG	49 Cu.ft	33~41°F	54.1*30.7*81.9	115V/60Hz	8	ETL,Energy Star
WKR-82B	72 Cu.ft	33~41°F	82.7*30.7*81.9	115V/60Hz	9	ETL,Energy Star
WKF-82B	72 Cu.ft	-8 ~0°F	82.7*30.7*81.9	115V/60Hz	9	ETL,Energy Star
WKR-82BG	72 Cu.ft	33~41°F	82.7*30.7*81.9	115V/60Hz	12	ETL,Energy Star

Salad Prep Table Refrigerator Conatiners and Cutting Board Includes

WKSR-27B

WKSR-48B

WKSR-60B

WKSR-72B

WKSR-27BM

WKSR-48BM

WKSR-60BM

WKSR-72BM

Features

- Precise fan cooling system keeps food at safe temperature.
- Stainless steel interior and exterior,and with anti fringeprint function.
- Preinstalled heavy duty castors with brakes.
- Self-closing doors with 90 degree stay-open feature.Locks and keys included.

Certifications

Intertek Intertek

Technical Data

Model	Gross Capacity	Tempertaure	Dimension WxDxH inch	Voltage	Pans Qty	Certications
WKSR-27B	7.4 Cu.ft	33~41°F	28.1*30*42.4	115V/60Hz	1/6x6+1/9x2	ETL
WKSR-27BM	7.4 Cu.ft	33~41°F	28.1*33.9*46	115V/60Hz	1/6x9+1/9x3	ETL
WKSR-48B	12.9 Cu.ft	33~41°F	48x30*42.4	115V/60Hz	1/6x12	ETL
WKSR-48BM	12.9 Cu.ft	33~41°F	48*33.9*46	115V/60Hz	1/6x18	ETL
WKSR-60B	16.4 Cu.ft	33~41°F	60*30*42.4	115V/60Hz	1/6x16	ETL
WKSR-60BM	16.4 Cu.ft	33~41°F	60*33.9*46	115V/60Hz	1/6x24	ETL
WKSR-72B	20 Cu.ft	33~41°F	72*30*42.4	115V/60Hz	1/6x18	ETL
WKSR-72BM	20 Cu.ft	33~41°F	72*33.9*46	115V/60Hz	1/6x30	ETL

Commercial Grade Under Counter Refrigerator and Freezer

Features

- Precision ventilated refrigertion system keeps food fresh.
- Eletronic control system make it easy to adjust temperature setponit and defrost frequency.
- Self closing door with 90 degree stay open feature, locks and keys included.
- Preinstalled heavy duty casters with brakes.
- Stainless steel exterior and interior, guaranteed to last up to 10 years and beyond.
- Paired with a durable copper coil evaporator, Westlake products are ensure surpassing 10 years of reliable performance.
- 1 epoxy coated steel wire shelf,90 lbs loading capacity each.

WKTR-27B
WKTF-27B

WKTR-48B
WKTF-48B

WKTR-60B
WKTF-60B

WKTR-72B
WKTF-72B

Certifications

Intertek Intertek DOE DOE ENERGY STAR

Technical Data

Model	Gross Capacity	Tempertaure	Dimension WxDxH inch	Voltage	Shelves	Certications
WKTR-27B	6.3 Cu.ft	33~41°F	28.1*29.9*34.2	115V/60Hz	1	ETL,Energy Star
WKTF-27B	6.3 Cu.ft	-8 ~0°F	28.1*29.9*34.2	115V/60Hz	1	ETL,DOE
WKTR-48B	11.9 Cu.ft	33~41°F	48*29.9*34.2	115V/60Hz	2	ETL,Energy Star
WKTF-48B	11.9 Cu.ft	-8 ~0°F	48*29.9*34.2	115V/60Hz	2	ETL,DOE
WKTR-60B	14.8 Cu.ft	33~41°F	60.2*29.9*34.2	115V/60Hz	2	ETL,Energy Star
WKTF-60B	14.8 Cu.ft	-8 ~0°F	60.2*29.9*34.2	115V/60Hz	2	ETL,DOE
WKTR-72B	17.7 Cu.ft	33~41°F	72*29.9*34.2	115V/60Hz	3	ETL,Energy Star
WKTF-72B	17.7 Cu.ft	-8 ~0°F	72*29.9*34.2	115V/60Hz	3	ETL,DOE

Open Air Merchandiser
Modular Ice Machine Full Cubic Ice

LD3-2Z-C1 LD3-2Z-C2 LD3-2Z-C3 LD3-2Z-C4

Features

- Precise fan cooling system keeps food at safe temperature.
- Bright, cool LED lighting to illuminate product; top-mounted lightbox to attract attention.
- Painted steel exterior and interior.

Certifications

Intertek Intertek

Technical Data

Model	Tempertaure	Dimension WxDxH inch	Voltage	Shelves	Cooling Mode	Certications
LD3-2Z-C1	33~39°F	27.6*28.4*79.5	115V/60Hz	4	Air cooled	ETL
LD3-2Z-C2	33~39°F	35.4*32.5*80.5	115V/60Hz	4	Air cooled	ETL,NSF
LD3-2Z-C3	33~39°F	45.7*32.5*81.4	115V/60Hz	4	Air cooled	ETL,NSF
LD3-2Z-C4	33~39°F	45.7*25.6*81.4	115V/60Hz	4	Air cooled	ETL,NSF

SK-329 SK-529

Features

- Exquisite Sheet Metal Craftsmanship,the frame structure is riveted withoutwelding.
- Anticorrosive chemical nickel plated evaporator.
- Digital control panel with fault code remind and ice thickness adjust function.
- Both side air filter design is easy for cleaning and changing.

Certifications

Intertek Intertek ENERGY STAR

Technical Data

Model	Output Capacity	Ice storage	Dimension WxDxH inch	Voltage	Cooling Mode	Certications
SK-329	350lbs/24H	275lbs	23.7*33.7*67.3	115V/60Hz	Air cooled	ETL,Energy Star
SK-529	500lbs/24H	375lbs	26.9*33.9*67.3	115V/60Hz	Air cooled	ETL,Energy Star

Commercial Gas Counter top Hotplate and Stockpot
Natural Gas and Liquid Propone Series

Features

- Capitalize on cooking space with independent burners to allow for maximum productivity.
- Standing pilots provide instant ignition for ease of use.
- Durable stainless steel front body withstands tough kitchen environments.
- Field convertible to liquid propane; orifices included.
- 25,000BTU/Burner for hotplate,80,000BTU/Burner for stockpot with NG; 3/4" rear gas connection.
- Removable waste tray that makes clean-up quick and easy.
- Stockpot is for a durable and reliable cooking solution.
- Stainless steel adjustable heavy duty legs.

Hot plate EHP-2S

Hot plate EHP-4S

Hot plate EHP-6S

Stockpot SP-1M

Stockpot SP-2M

Certifications

Intertek Intertek

Technical Data

Model	Description	Grate size(inch)	Total input(Btu/hr)	Product size(WxDxH) inch	Net weight	Certications
EHP-2S	Hotplate	12*12	50,000	11.8*27.2*13.4	70 lbs	ETL,NSF
EHS-4S	Hotplate	12*12	100,000	23.6*27.2*13.4	125 lbs	ETL,NSF
EHS-6S	Hotplate	12*12	150,000	35.4*27.2*13.4	183 lbs	ETL,NSF
SP-1M	Stockpot	18*18	80,000(NG)/50,000(LP)	18*21*19	103 lbs	ETL,NSF
SP-2M	Stockpot	18*18	160,000(NG)/100,000 (LP)	18*41*19	198 lbs	ETL,NSF

Commercial Gas Stand Free Deep Fryer
Natural Gas Series

GF-90N

GF-120N

GF-150N

Features

- Stainless steel tank,front and galvanized sides and back.
- Vertical cast iron burner,each 30,000 Btu/hr.
- Tube design with baffles inside for better heat transfer.
- Continuous pilot for easy start of main flame.
- 2 chromed baskets with plastic coating handles.
- Large cold zone to prevent scorching of food particles at the bottom.
- Prompt temperature recovery to make sure fries are crispy.
- 1¼ drain cock for easy drainage of oil.
- Thermostat adjusts from 200°F to 400°F.

Certifications

Intertek Intertek

Technical Data

Model	Description	Oil storage capacity	Total input(Btu/hr)	Product size(WxDxH) inch	Net weight	Certications
GF90-N	Deep fryer	40lbs	90,000	15.5*30.2*46.5	143 lbs	ETL,NSF
GF120-N	Deep fryer	50lbs	120,000	15.5*30.2*46.5	156 lbs	ETL,NSF
GF150-N	Deep fryer	70lbs	150,000	21*30.2*46.5	172 lbs	ETL,NSF

Commercial Gas convection Oven
Natural Gas and Liquid propone Series

GCO511

GCO511S

Features

- Stainless steel front, galvanized sides with robust support.
- Stainless steel tube burners,Temperature adjustable from 167°F to 563°F.
- Porcelainized interior, easy to clean, Dual pane thermal glass windows.
- 60-minute electric timer with bell.
- Double circulating fan,deep depth(25-3/8") oven cavity,Removable 11-position rack guides.
- 4 heavy duty chrome plated racks.
- Cooling down function and Interior chamber light.
- Double stacking options to optimize kitchen space.
- Automaticignition system for gas safety operation.
- Micro switch for complete shut off once door is opened.
- 3/4" NPT rear gas connection.

Certifications

Intertek Intertek

Technical Data

Model	Description	Voltage/Amp	Total input(Btu/hr)	Product size (WxDxH)inch	Net weight	Certications
GCO511	Convention Oven	115V,60hz,9.3A	60,000(NG) 52,000(LP)	39*39.6*56	460 lbs	ETL,NSF
GCO511S	Convention Oven	115V,60hz,9.3A*2	60,000(NG)*2/52,000(LP)*2	39*39.6*70.7	929 lbs	ETL,NSF

Commercial Gas Counter top Griddle
Natural Gas and Liquid Propone Series

Features

- U-shape steel burner, each 30,000 BTU/hr.
- Standby pilot for easy start.
- Stainless steel adjustable heavy duty legs.
- Large oil collector at the bottom.
- Easy conversion from natural gas to Propane or vice versa.
- Stainless steel in the front, and galvanized sides and back.
- 5/8"thickness griddle plate and manual control,reduced recovery time.

EGG16S

EGG24S

EGG36S

EGG48S

EGG60S

Certifications

Intertek Intertek

Technical Data

Model	Description	Total input(Btu/hr)	Product size(WxDxH) inch	Net weight	Certications
EGG16S	Gas Griddle	30,000	15.9*25.2*15.4	90 lbs	ETL,NSF
EGG24S	Gas Griddle	60,000	23.8*25.2*15.4	114 lbs	ETL,NSF
EGG36S	Gas Griddle	90,000	35.6*25.2*15.4	176 lbs	ETL,NSF
EGG48S	Gas Griddle	120,000	47.4*25.2*15.4	297 lbs	ETL,NSF
EGG60S	Gas Griddle	150,000	59.2*25.2*15.4	308 lbs	ETL,NSF

Commercial Gas Counter top Radiant broiler
Natural Gas and Liquid Propone Series

ECB16S

ECB24S

ECB36S

ECB48S

ECB60S

Features

- U-shape steel burner, each 30,000 BTU/hr.
- Standby pilot for easy start.
- Stainless steel adjustable heavy duty legs.
- Large oil collector at the bottom.
- Easy conversion from natural gas to Propane or vice versa.
- Stainless steel in the front, and galvanized sides and back.
- Cast iron grate and manual control.

Certifications

Intertek Intertek

Technical Data

Model	Description	Total input(Btu/hr)	Product size(WxDxH) inch	Net weight	Certications
ECB16S	Gas Radiant Broiler	30,000	15.9*25.2*15.4	108 lbs	ETL,NSF
ECB24S	Gas Radiant Broiler	60,000	23.8*25.2*15.4	119 lbs	ETL,NSF
ECB36S	Gas Radiant Broiler	90,000	35.6*25.2*15.4	163 lbs	ETL,NSF
ECB48S	Gas Radiant Broiler	120,000	47.4*25.2*15.4	216 lbs	ETL,NSF
ECB60S	Gas Radiant Broiler	150,000	59.2*25.2*15.4	268 lbs	ETL,NSF

Commercial Gas Burner With Oven
Natural Gas and Liquid Propone Series

Features

- Fully MIG welded frame for stability.
- Stainiess steel front, back-riser, galvanized sides.
- 6"stainless steel adjustable heavy duty legs.
- Open top burners, each 30,000 BTU/hr.
- Coved pilot burner cover to prevent clogging from spillage.
- Stainless steel pilot for durability.
- Heavy duty cast grates,12"x12" in size, easy to be removed.
- Pull out crumb tray with rounded edges to prevent heat transfer.
- 31,000 BTU/hr U-shape burner for bottom oven.
- Full size sheet pans fit side-to-side or front-to-back.
- Oven thermostat adjusts from 250°F to 550°F.
- Two oven racks and four rack positions.

RGR24

RGR36

Certifications

Intertek Intertek

Technical Data

Model	Description	Total input(Btu/hr)	Product size(WxDxH) inch	Net weight	Certications
RGR24	Gas Burner With Oven	Buner 30,000*4 Btu/hr Oven 31,000 Btu/hr	24*32.7*60	290 lbs	ETL,NSF
RGR36	Gas Burner With Oven	Buner 30,000*6 Btu/hr Oven 31,000 Btu/hr	36*32.6*60	367 lbs	ETL,NSF